



JKL LAMP PART NO.	COLOR RGB WHITE REF. 9700°k	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF20185-25B	x = 0.28 ± 0.02 y = 0.26 ± 0.02	1050 @ 0°C	420	5	35,000 TYP.	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

NOTE 1: MERCURY (Hg) CONTENT: 2.4mg/LAMP MAX.

<p>THIRD ANGLE PROJECTION</p>			<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.2</p> <p>2 PL +/- 0</p> <p>ANGLE +/- 0</p>		<p>JKL COMPONENTS CORPORATION</p> <p>TITLE: MINIATURE COLD CATHODE FLUORESCENT LAMP</p>				
<p>DRAWN BY: L. WENGSTROM</p>			<p>APPVD BY: L.R.</p> <p>DATE: 7/30/09</p>		<p>SIZE: A</p>	<p>FSCM NO.: 55335</p>	<p>DRAWING NO.: BF20185-25B</p>		
<p>RATED LIFE HRS MINIMUM: 20,000</p> <p>ENGINEERING RELEASE & CANCEL P-0505-02</p>			<p>DATE: 7/30/09</p> <p>DATE: 11/23/05</p>		<p>- CAD DRAWING -</p> <p>MANUAL REVISIONS NOT PERMITTED</p>				
<p>REV. NO.</p>	<p>DESCRIPTION/ECO NUMBER</p>	<p>APPVD DATE</p>	<p>SCALE: NONE</p>		<p>RELEASED DATE: 11/23/05</p>	<p>REVISION DATE: 7/30/09</p>	<p>REV. NO.: A</p>	<p>SHEET 1 OF 1</p>	